

# Ultrascreen PRO 1000 light blue FG DUPLEX

Article code: USBE002011

## General information

<b>Product group</b>	Ultrascreen
<b>Main product feature</b>	Positive drive, Chemical resistant, Non-stick, Wear resistant

## Belt construction

<b>Material</b>	TPE
<b>Color</b>	Light blue

## Characteristics

<b>Food Grade (FG)</b>	yes	EU 1935/2004, EU 10/2011; FDA
------------------------	-----	-------------------------------

## Technical data

<b>Belt thickness</b>			1.50 mm	0.06 in.
<b>Weight</b>			0.825 kg/m <sup>2</sup>	0.17 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from / to	-15 / 70 °C	5 / 158 °F
	short	from / to	-15 / 70 °C	5 / 158 °F
<b>Minimum pulley diameter</b>	flexing		143.5 mm	5.65 in.
	backflexing		225 mm	8.86 in.
<b>Manufacturing length</b>	maximum		40000 mm	1574.8 in.
<b>Manufacturing width</b>	maximum		1450 mm	57.09 in.
	standard		1450 mm	57.09 in.

## Fabrication

<b>Recommended splice method</b>	Ultrascreen
----------------------------------	-------------

## Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

Keep the belt tension to a practical working minimum for maximum belt and machine life.

Store loose and wrapped in plastic. The allowable product temperature may vary.