

Plastic Chain Series - Product Overview



Slat Top Chains

Straight Running Chains

<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>uni 820 831 Strength: 2000 N (449 lbf)</p>	<p>uni 820 Vacuum Strength: 2000 N (449 lbf)</p>	<p>AVE 828 Strength: 2150 N (483 lbf)</p>	<p>uni 821 Strength: 3000 N (674 lbf)</p>



<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>uni 821 LBP Strength: 3000 N (674 lbf)</p>	<p>AVE 8257 Strength: 3900N (877 lbf)</p>	<p>AVE 8257 LBP Strength: 3900N (877 lbf)</p>	<p>AVE 900 Strength: 1750 N (393 lbf)</p>

Side Flexing Magnetic

<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>AVE 879 M Strength: 2150 N (483 lbf) Min. Radius: 457 mm (17.99 in)</p>	<p>AVE 880 M Strength: 2150 N (483 lbf) Min. Radius: 457 mm (17.99 in)</p>	<p>AVE 882 M Strength: 3900 N (877 lbf) Min. Radius: 610 mm (24,02 in)</p>	<p>AVE 882 M LBP Strength: 3900 N (877 lbf) Min. Radius: 610 mm (24,02 in)</p>

Slat Top Chains

Side Flexing Chains

<p>Pitch 19.1 mm (0.75 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>uni 440 Tab</p> <p>Strength: 1100 N (247 lbf) Min. Radius: 175.0 mm (6.89 in)</p>	<p>uni 879 BEVEL</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 400 mm (15.75 in)</p>	<p>uni 879 Tab* Tab R</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 400.0 mm (15.75 in)* 200.0 mm (7.87 in)</p>	<p>uni 879 Tab Safety Finger</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 200.0 mm (7.87 in)</p>
<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>uni 879 Tab Safety</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 200.0 mm (7.87 in)</p>	<p>uni 879 Tab R G4</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 200.0 mm (7.87 in)</p>	<p>uni 880 BEVEL</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 400.0 mm (15.75 in)</p>	<p>uni 880 Tab* Tab R</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 400.0 mm (15.75 in)* 200.0 mm (7.87 in)</p>
<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>uni 880 Tab Vacuum</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 400.0 mm (15.75 in)*</p>	<p>uni 880 Tab RT</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 200.0 mm (7.87 in)</p>	<p>uni 880 Super Flex</p> <p>Strength: 2250 N (506 lbf) Min. Radius: 457.0 mm (17.99 in) 610.0 mm (24.02 in)</p>	<p>uni 882 Tab</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 610.0 mm (24.02 in) 700.0 mm (27.56 in)</p>
<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 	<p>Pitch 38.1 mm (1.50 in)</p> 
<p>uni 882 TAB RT</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 610.0 mm (24.02 in) 700.0 mm (27.56 in)</p>	<p>uni 882 Tab SC</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 610.0 mm (24.02 in)</p>	<p>AVE 882 TAB LBP</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 610.0 mm (24.02 in)</p>	<p>AVE 887 Tab</p> <p>Strength: 3000 N (674 lbf) Min. Radius: 500 mm (19.69 in)</p>

Snap On Chains

Straight Running Chains

<p>Pitch 12.7 mm (0.50 in)</p> 	<p>Pitch 19.1 mm (0.75 in)</p> 	<p>Pitch 19.1 mm (0.75 in)</p> 
<p>uni 843 SK</p> <p>Strength SS: 1500 N (340 lbf) Strength carbon: 2000 N (450 lbf)</p>	<p>uni 863 Tab</p> <p>Strength SS: 2700 N (600 lbf) Strength carbon: 5500 N (1200 lbf)</p>	<p>uni 963</p> <p>Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf)</p>



Side Flexing Chains

<p>Pitch 12.7 mm (0.50 in)</p> 	<p>Pitch 12.7 mm (0.50 in)</p> 	<p>Pitch 19.1 mm (0.75 in)</p> 
<p>uni 1843 TAB</p> <p>Strength SS: 1500 N (340 lbf) Strength carbon: 2000 N (450 lbf) Min. Radius: 254 mm (10.0 in)</p>	<p>AVE 1843 Grip G3</p> <p>Strength SS: 1900 N (427 lbf) Strength carbon: 2700 N (607 lbf) Min. Radius: 350 mm (13.78 in)</p>	<p>uni 1873 TAB</p> <p>Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min radius: 356 mm (14.02 in) 457 mm (17.99 in)</p>

<p>Pitch 19.1 mm (0.75 in)</p> 	<p>Pitch 19.1 mm (0.75 in)</p> 	<p>Pitch 19.1 mm (0.75 in)</p> 
<p>uni 1873 Grip G3 Grip G4 Grip G4L</p> <p>Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min. Radius: 356 mm (14.02 in)</p>	<p>uni 1873 Grip D</p> <p>Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min. Radius: 356 mm (14.02 in)</p>	<p>uni 3873 TAB</p> <p>Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min. Radius: 356 mm (14.02 in)</p>

Case Chains



Straight Running Chains

Pitch 66.3 mm (2.61 in)	Pitch 50.8 mm (2.00 in)
	
<p>uni NH78</p> <p>Strength: T1: 9000 N (2023 lbf) T2: 7000 N (1574 lbf) T3: 6000 N (1349 lbf) T4: 6000 N (1349 lbf) T5: 5000 N (1124 lbf)</p>	<p>uni 3200</p> <p>Strength: 3150 N (708 lbf)</p>

Side Flexing Chains

Pitch 50.8 mm (2.00 in)	Pitch 63.5 mm (2.50 in)	Pitch 63.5 mm (2.50 in)
		
<p>uni 3200 Tab</p> <p>Strength: 2525 N (568 lbf) Min. Radius: 406.0 mm (16.00 in)</p>	<p>uni 2600 C Tab C</p> <p>Strength: 6000 N (1686 lbf) Min. Radius: 600.0 mm (23.62 in)</p>	<p>uni 2600 O Tab O</p> <p>Strength: 6000 N (1686 lbf) Min. Radius: 600.0 mm (23.62 in)</p>

Pitch 63.5 mm (2.50 in)	Pitch 63.5 mm (2.50 in)	Pitch 70.0 mm (2.76 in)
		
<p>uni 2500</p> <p>Strength: 7500 N (1686 lbf) Min. Radius: 600.0 mm (23.62 in)</p>	<p>AVE 610 ML</p> <p>Strength: 3000 N (674 lbf) Min. Radius: 80mm (3.15in)</p>	<p>uni 2700</p> <p>Strength: 11000 N (2473 lbf) Min. Radius: 300.0 mm (1181 in)</p>

Pitch 82.5 mm (3.25 in)	Pitch 82.5 mm (3.25 in)
	
<p>uni 1400 Tab</p> <p>Strength: 8000 N (1798 lbf) Min. Radius: 450 mm (17.72 in)</p>	<p>uni 2800 Tab</p> <p>Strength: 6000 N (1349 lbf) Min. Radius: 500.0 mm (19.69 in)</p>





Multi Flex Chains

Side Flexing Chains

<p>Pitch 50.0 mm (1.97 in)</p> 	<p>Pitch 50.0 mm (1.97 in)</p> 	<p>Pitch 50.0 mm (1.97 in)</p> 	<p>Pitch 50.0 mm (1.97 in)</p> 
<p>uni 1700</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 150.0 mm (5.91 in)</p>	<p>uni 1701 Tab Tab R*</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 150.0 mm (5.91 in) 125.0 mm (4.92 in)*</p>	<p>uni 1702</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 150.0 mm (5.91 in)</p>	<p>uni 1702 M</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 150.0 mm (5.91 in)</p>
<p>Pitch 50.0 mm (1.97 in)</p> 	<p>Pitch 50.0 mm (1.97 in)</p> 	<p>Pitch 50.0 mm (1.97 in)</p> 	<p>Pitch 50.0 mm (1.97 in)</p> 
<p>uni 1703</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 150.0 mm (5.91 in)</p>	<p>uni 1704</p> <p>Strength: 4000 N (899 lbf) Min. Radius: 137.5 mm (5.41 in)</p>	<p>uni 1705</p> <p>Strength: 3100 N (689 lbf) Min. Radius: 136.0 mm (5.35 in)</p>	<p>uni 1706</p> <p>Strength: 3100 N (689 lbf) Min. Radius: 150.0 mm (5.91 in)</p>
<p>Pitch 50.0 mm (1.97 in)</p> 			
<p>AVE 1700 Finger Protection</p> <p>Strength: 2700 N (607 lbf) Min. Radius: 150.0 mm (5.91 in)</p>			

Chains Belts

Side Flexing Chains

<p>Pitch 25,4 mm (1 in)</p> 	<p>Pitch 25,4 mm (1 in)</p> 	<p>Pitch 25,4 mm (1 in)</p> 	<p>Pitch 25,4 mm (1 in)</p> 
<p>uni 253 FT BEVEL Strength: 1900 N (427 lbf) Min. Radius: 500 mm (19.68 in)</p>	<p>uni 253 FT TAB 255 FT TAB Strength: 1900 N (427 lbf) Min. Radius: 500 mm (19.68 in)</p>	<p>uni 253 FT M 255 FT M Strength: 1900 N (427 lbf) Min. Radius: 500 mm (19.68 in)</p>	<p>uni 253 FG M Strength: 1900 N (427 lbf) Min. Radius: 500 mm (19.68 in)</p>

<p>Pitch 25,4 mm (1 in)</p> 	<p>AVE 7253 Tab Strength: 3100 N (697 lbf) Min. Radius: 500 mm (19.68 in)</p>
---	--

Local Contacts

... and 150 more service contact points
at ammeraalbeltech.com

Argentina

T +54 11 4218 2906
info-ar@ammeraalbeltech.com

Australia

T +61 3 8780 6000
info-au@ammeraalbeltech.com

Austria

T +43 171728 133
info-de@ammeraalbeltech.com

Belgium

T +32 2 466 03 00
info-be@ammeraalbeltech.com

Canada

T +1 905 890 1311
info-ca@ammeraalbeltech.com

Chile

T +56 22 656 1600
info-cl@ammeraalbeltech.com

China

T +86 512 8287 2709
info-cn@ammeraalbeltech.com

Colombia

T +57 1 893 9890
info-co@ammeraalbeltech.com

Czech Republic

T +420 567 117 211
info-cz@ammeraalbeltech.com

Denmark

T +45 7572 3100
info-dk@ammeraalbeltech.com

Finland

T +358 207 911 400
info-fi@ammeraalbeltech.com

France

T +33 3 20 90 36 00
info-fr@ammeraalbeltech.com

Germany

T +49 4152 937-0
info-de@ammeraalbeltech.com

Hungary

T +36 30 311 6099
info-hu@ammeraalbeltech.com

India

T +91 44 265 34 244
info-in@ammeraalbeltech.com

Israel

T +972 4 6371485
info-il@ammeraalbeltech.com

Italy

T +39 051 660 60 06
info-it@ammeraalbeltech.com

Japan

T +81 52 433 7400
info-jp@ammeraalbeltech.com

Luxembourg

T +352 26 48 38 56
info-lu@ammeraalbeltech.com

Malaysia

T +60 3 806 188 49
info-my@ammeraalbeltech.com

Mexico

T +52 55 5341 8131
info-mx@ammeraalbeltech.com

Netherlands

T +31 72 57 51212
info-nl@ammeraalbeltech.com

Peru

T +51 1 713 0069
info-pe@ammeraalbeltech.com

Poland

T +48 32 44 77 179
info-pl@ammeraalbeltech.com

Portugal

T +351 22 947 94 40
info-pt@ammeraalbeltech.com

Singapore

T +65 62739767
info-sg@ammeraalbeltech.com

Slovakia

T +421 255648542
info-sk@ammeraalbeltech.com

South Korea

T +82 31 448 3613-7
info-kr@ammeraalbeltech.com

Spain

T +34 93 718 3054
info-es@ammeraalbeltech.com

Sweden

T +46 (0) 10 130 96 00
info-se@ammeraalbeltech.com

Switzerland

T +41 55 225 35 35
info-ch@ammeraalbeltech.com

Thailand

T +66 2 902 2604-13
info-th@ammeraalbeltech.com

Turkey

T +90 232 877 0700
info-tr@ammeraalbeltech.com

United Kingdom

T +44 1992 500550
info-uk@ammeraalbeltech.com




United States

T +1 847 673 6720
info-us@ammeraalbeltech.com

Vietnam

T +84 8 376 562 05
info-vn@ammeraalbeltech.com

**Expert advice, quality solutions
and local service
for all your belting needs**



General contact information:

Ammeraal Beltech
P.O. Box 38
1700 AA Heerhugowaard
The Netherlands

T +31 (0)72 575 1212
info@ammeraalbeltech.com

ammera.com