




ZipLink® Belts

Win your race at the pit stop!





ZipLink® Belts makes your production run eliminating all issues related to belt splicing!

Ammeraal Beltech is a leading manufacturer of process and conveyor belts with an established reputation for developing innovative solutions for belting applications.

Working closely with OEMs and end users Ammeraal Beltech has developed a range of ZipLink® Belts: a special design link fabric in combination with top covers giving superior performance. Main benefit is the striking increase of your production time.



Scan the QR Code and watch the video!

Features	Benefits
Increased production time	<ul style="list-style-type: none"> • Shortest production downtime • Reduced maintenance time and cost • Extended belt service life
Operational safety	<ul style="list-style-type: none"> • Protects both product and conveyor from being damaged • Extra high stability allows for easier tracking
Less energy consumption	<ul style="list-style-type: none"> • Low friction bottom version helps reduce energy
Economical use	<ul style="list-style-type: none"> • Strongest in-house splicing; no outside fitters required • No need for any special tools or presses • Possible repair of damaged belt sections
Proven technology	<ul style="list-style-type: none"> • Choice of top cover materials tuned to the application

ZipLink® is an innovative belt range which is specially designed to offer **benefits in a variety of different industries**. Quick and simple installation or repair help to lower costs and reduce downtime. The design allows for repair or replacement of just small sections of the belt.










Joint with one single pin!



Download the Case Studies



ZipLink® is an innovative Belting Concept allowing easy customisation!

Materials	General characteristics	Main applications	Examples
Natural Rubber	<ul style="list-style-type: none"> • Thermoset rubber • Excellent abrasion resistance • Excellent grip in wet and dry characteristics • FDA • Temperature range -40 °C to 121 °C 	Paper and Cardboard Industry Wood Industry Inclined transportation Tobacco Industry Agriculture	
Carboxylated Rubber	<ul style="list-style-type: none"> • Thermoset rubber • Excellent abrasion resistance • Excellent oil and fat resistance • Good grip in wet and dry characteristics • Temperature range -18 °C to 121 °C 	Paper and Cardboard Industry Wood Industry Sugar Industry Detergent powder Metal Industry	
Nitrile	<ul style="list-style-type: none"> • Thermoset rubber • Excellent oil and fat resistance • Wear and impact-resistance • FDA/USDA • Temperature range -18 °C to 121 °C 	Food processing (Meat & Poultry, Fish and Corn Flakes) Chemical Industry Textile (roll covering) Cardboard production	
SBR	<ul style="list-style-type: none"> • Thermoset rubber • Good abrasion resistance • Excellent grip • Economical • Temperature range -40 °C to 121 °C 	General package handling Airport Industry (inside and outside terminal) Brick and Tile Industry Chemical Industry Carton Industry	
Silam	<ul style="list-style-type: none"> • Thermoset rubber • Excellent release properties • Good chemical resistance • FDA/USDA • Temperature range -54 °C to 176 °C continuous, -58 °C to 260 °C intermittent 	Tyre Industry (mixing department) Chemical Industry Shrink tunnels Food processing Leather and textile	
Teflon	<ul style="list-style-type: none"> • Thermoplastic • Excellent release properties • Excellent chemical and stain resistance • Good oil and fat resistance • FDA • Temperature range -50 °C to 82 °C 	Extrusion Industry Food Industry Chemical Industry Fiberglass Industry	
Cotton / Felt	<ul style="list-style-type: none"> • Temperatures up to 120 °C 	Tyre Industry Cardboard Metal stamping Car Industry Aluminum extrusion	

ZipLink® is a breakthrough in belting design that combines cover materials with a structured link mesh that can be easily spliced at any length into a continuous belt without the need for special tools, presses or other equipment.


The ZipLink® construction eliminates points of weakness because there is no loss of strength in the splice area, making the belts stronger so they last longer than belts of other seamed or fused materials.

ZipLink® provides long life and flexibility for multiple applications. The belts can easily and quickly be changed without accruing significant downtime or expensive overtime. After converting to ZipLink®, time and personnel required to change belts may be reduced by more than half.



Complete toolbox available, including instruction CD


Working instruction



Scan the QR Code and watch the video!




Score the back and lubricate the pin.




Pop the pin out at 1.5 cm from the edge.




Gently pull the pin out using pliers.




Carefully cut the top cover.



Press the ends back together firmly.




Pass the wire through and cut the excess.




Synthetic Belts



Endless Woven Belts



Modular Belts



Engineered Belts



Homogeneous Belts



Fabrication & Service

Expert advice and quality solutions for all your belting needs.
ammeraalbeltech.com

Ammeraal Beltech
 P.O. Box 38
 1700 AA Heerhugowaard
 The Netherlands

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.

T +31 (0)72 575 1212
info@ammeraalbeltech.com